



cod.	Ø	pz/pcs	C	ØG	sp	bullone	cusc	binario	portata
402.40	40	12	16	Ø33	12	M8x30	1	-	60 kg.
402.50	50	12	16	Ø39	13	M8x30	1	-	80 kg.
402.60	60	12	24	Ø46	17	M10x45	1	-	100 kg.
402.70	70	6	33	Ø52	20	M14x70	1	906	190 kg.
402.80	80	6	33	Ø62	20	M14x70	1	906	200 kg.
402.90	90	6	33	Ø72	21	M14x70	1	906	210 kg.
402.100	100	6	33	Ø82	21	M14x70	1	906	230 kg.
402.120	120	4	33	Ø100	24	M14x70	1	906	250 kg.
402.140	140	4	43	Ø118	24	M16x70	1	906	280 kg.
402.160	160	2	43	Ø138	25	M16x70	1	906	300 kg.
402.200	200	2	43	Ø178	25	M16x70	1	906	340 kg.



Sliding gates accessories



Galvanized steel components



- Components to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

